



**INTERNATIONAL  
FASTENERS, INC.**

## Star Trim Head with Nibs

### Type 17 Point

### Tan ACQ Dagger Ultra-Guard Coating™

Size	TPI	Part #	QTY / Carton	Drive
7 x 1-5/8"	9	ACQTST07158	5,000 pcs	T-15 Star
7 x 2-1/4"	9	ACQTST07214	3,000 pcs	T-15 Star
8 x 3"	9	ACQTST08300	2,000 pcs	T-15 Star

**material:** C1022 Low Carbon Steel, Core Hardness: HV240-425

**finish:** Dagger Ultra-Guard Coating™ is a zinc/chromate substrate with proprietary organic topcoat, multi step process for use with ACQ treated lumber provides 1000 hour salt spray corrosion resistance

**application:** Wood to wood in exterior applications

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

#### Meet or exceeds the following specifications:

<b>ASME B18.6.1</b>	Specification for wood screws
<b>ASTM A510</b>	Specification for general requirements for carbon steel wire rods (Minimum grade 1018)
<b>ASTM B117</b>	Standard practice for operating salt spray (fog) apparatus
<b>ASTM F1941</b>	Specification for electrodeposited coatings on threaded fasteners

#### Ultimate Values

Diameter	3/4" Particle Board Pullout (lb)	2 x 4 Redwood Pullout (lb)	2 x 4 Fir Pullout (lb)	Minimum Torsional Strength (lb)
<b>#7</b>	298	273	465	30
<b>#8</b>	290	518	540	39

ACQTST | Revision 1.0 | 03.13.25

