



**INTERNATIONAL
FASTENERS, INC.**

Hex Head with EPDM Bonded Washer

Type AB Point

Dagger-Guard Coating™



Size	TPI	Part #	QTY / Carton	Drive
17 x 1"	14	DAGCT1710TAB	2,000	3/8" Hex
17 x 1-1/2"	14	DAGCT17112TAB	1,500	3/8" Hex

material: C1022 Low Carbon Steel, Core Hardness: HV240-425

finish: Dagger-Guard Coating™ is a three layer, multi step dip/spin/bake process which provides 1000 hour salt spray corrosion resistance

application: Metal to wood applications, used to replace 1/4" diameter fasteners where the threads have stripped out

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

ASTM C1002 Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

ASTM F1941 Specification for electrodeposited coatings on threaded fasteners

Ultimate Values

	Diameter	26 Gauge	24 Gauge	22 Gauge	20 Gauge	18 Gauge	16 Gauge	14 Gauge
Tension (lb) Pullout	#17	225	261	350	442	553	752	1122
Shear (lb) Bearing	#17	459	745	989	958	1415	-	-

DAGCTTAB | Revision 1.0 | 08.19.25