



**INTERNATIONAL  
FASTENERS, INC.**

## Hex Zinc Alloy Cap with EPDM Bonded Washer

### Hi-Low Thread, Type 17 Point

### Dagger-Guard Coating™



Size	TPI	Part #	QTY / Carton	Drive
10 x 1-1/2"	14	DAGCTZ10112T17	2,000	1/4" Hex

**material:** C1022 Low Carbon Steel. Core Hardness: HV240-425

**finish:** Dagger-Guard Coating™ is a three layer, multi step dip/spin/bake process which provides 1000 hour salt spray corrosion resistance

**application:** Metal to wood applications

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

#### Meet or exceeds the following specifications:

**ASTM A510** Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

**ASTM B117** Standard practice for operating salt spray (fog) apparatus

**ASTM B663** Standard specification for electrodeposited coatings of zinc on iron and steel

**ASTM F1941** Specification for electrodeposited coatings on threaded fasteners

#### Ultimate Values

	Diameter	2 x 4 Fir	25 Gauge	20 Gauge	Minimum Torsional Strength (lb)
<b>Tension (lb) Pullout</b>	#10	428	173	363	56
<b>Shear (lb) Bearing</b>	#10	-	397	834	56

DAGCTZ | Revision 1.0 | 08.20.25