



**INTERNATIONAL  
FASTENERS, INC.**

## Hex Washer Head with EPDM Bonded Washer

### Type 17 Point

### 304 Stainless Steel

Size	TPI	Part #	QTY / Carton	Drive
10 x 1-1/2"	14	DAGSSS10112T17	2,500	1/4" Hex

**material:** 304 Stainless Steel

**application:** Light metal exterior applications

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

#### Meet or exceeds the following specifications:

**ASME B 18.6.1** Standard specification for wood screws

**ASTM A276** Standard specification for stainless steel bars and shapes

**ASTM B117** Standard practice for operating salt spray (fog) apparatus

#### Ultimate Values

	Diameter	2 x 4 Fir	25 Gauge	20 Gauge	Minimum Torsional Strength (lb)
<b>Tension (lb) Pullout</b>	#10	428	173	363	56
<b>Shear (lb) Bearing</b>	#10	-	397	834	56

DAGSSS | Revision 1.0 | 08.20.25

