



**INTERNATIONAL
FASTENERS, INC.**

Star Button Head

Dual Thread, Type 17 Point

305 Stainless Steel

Size	TPI	Part #	QTY / Carton	Drive
10 x 2-1/2"	18/9	DKCSTSS10212	2,000	T-15 Star
10 x 3"	18/9	DKCSTSS1030	1,000	T-15 Star

material: 305 Stainless Steel

application: Composite deck applications in harsh exterior conditions

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASME B18.6.1 Specification for wood screws

ASTM A276 Standard specification for stainless steel bars and shapes

ASTM B117 Standard practice for operating salt spray (fog) apparatus

Ultimate Values

Diameter	3/4" Particle Board Pullout (lb)	2 x 4 Redwood Pullout (lb)	2 x 4 Fir Pullout (lb)	Minimum Torsional Strength (lb)
#10	388	587	563	56

DKCSTSS | Revision 1.0 | 08.30.25

