



**INTERNATIONAL
FASTENERS, INC.**

Star Flat Head with Nibs

Type 17 Point

Yellow Zinc Plated

Size	TPI	Part #	QTY / Carton	Drive
8 x 1-1/4"	9	DKSTY081104	7,500	T-25 Star
8 x 1-5/8"	9	DKSTY08158	5,000	T-25 Star
8 x 2"	9	DKSTY08200	3,500	T-25 Star
9 x 2-1/2"	8	DKSTY09212	2,500	T-25 Star
9 x 3"	8	DKSTY09300	1,500	T-25 Star
10 x 2-1/2"	8	DKSTY10212	2,500	T-25 Star
10 x 3"	8	DKSTY1030	1,500	T-25 Star
10 x 3-1/2"	8	DKSTY10312	1,000	T-25 Star
10 x 4"	8	DKSTY1040	1,000	T-25 Star
10 x 5"	8	DKSTY1050	1,000	T-25 Star
10 x 6"	8	DKSTY1060	1,000	T-25 Star

material: C1022 Low Carbon Steel, Core Hardness: HRC 28-38

finish: Yellow zinc plating with .0003" thickness provides 180 hour minimum salt spray corrosion

application: Wood to wood applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASME B18.6.1 Specification for wood screws

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

Ultimate Values

Diameter	3/4" Particle Board Pullout (lb)	2 x 4 Redwood Pullout (lb)	2 x 4 Fir Pullout (lb)	Minimum Torsional Strength (lb)
#8	290	518	540	39
#10	388	587	563	56

DKSTY | Revision 1.0 | 08.14.25

