



Square Trim Head with Nibs

Type 17 Point

305 Stainless Steel



Size	TPI	Part #	QTY / Carton	Drive
7 x 1-5/8"	9	DKTSS07158	5,000	#1 Square
7 x 2-1/4"	9	DKTSS07214	3,000	#1 Square
8 x 3"	9	DKTSS08300	2,000	#1 Square

material: 305 Stainless Steel

application: Wood to wood in harsh exterior applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASME B 18.6.1	Specification for wood screws
ASTM A276	Standard specification for stainless steel bars and shapes
ASTM B117	Standard practice for operating salt spray (fog) apparatus

Ultimate Values

Diameter	3/4" Particle Board Pullout (lb)	2 x 4 Redwood Pullout (lb)	2 x 4 Fir Pullout (lb)	Minimum Torsional Strength (lb)
#7	298	273	465	30
#8	290	518	540	39

DKTSS | Revision 1.0 | 08.30.25