



**INTERNATIONAL  
FASTENERS, INC.**

## Square Flat Head with Nibs

### Type 17 Point

### Black Oxide

Size	TPI	Part #	QTY / Carton	Drive
8 x 1"	9	DLFLSQB08100	10,000	#2 Square
8 x 1-1/4"	9	DLFLSQB081104	7,500	#2 Square
8 x 1-1/2"	9	DLFLSQB08112	5,000	#2 Square
8 x 1-5/8"	9	DLFLSQB081158	5,000	#2 Square
8 x 1-3/4"	9	DLFLSQB08134	4,000	#2 Square
8 x 2"	9	DLFLSQB08200	3,500	#2 Square
8 x 2-1/4"	9	DLFLSQB082104	3,000	#2 Square
8 x 2-1/2"	9	DLFLSQB08212	2,500	#2 Square
8 x 3"	9	DLFLSQB08300	1,500	#2 Square

**material:** C1022 Low Carbon Steel, Core Hardness: HV240-425

**finish:** Black oxide is a conversion coating which provides up to 48 hour salt spray corrosion resistance

**application:** Wood to wood applications

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

#### Meet or exceeds the following specifications:

**ASME B 18.6.1** Specification for wood screws

**ASTM A510** Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

**ASTM B117** Standard practice for operating salt spray (fog) apparatus

#### Ultimate Values

Diameter	3/4" Particle Board Pullout (lb)	2 x 4 Redwood Pullout (lb)	2 x 4 Fir Pullout (lb)	Minimum Torsional Strength (lb)
#8	290	518	540	39

DLFLSQB | Revision 1.0 | 10.10.25

