

**Threaded Rod
Plain**

Size	TPI	Part #	QTY / Bundle	FT / Total	LBS / Bundle
3/8 x 3'	16	ITRP03703	25	75'	21
3/8 x 6'	16	ITRP03706	25	150'	43
3/8 x 10'	16	ITRP03710	25	250'	72
1/2 x 6'	13	ITRP5006	12	72'	36
1/2 x 10'	13	ITRP5010	12	120'	62
1/2 x 12'	13	ITRP5012	12	144'	75
5/8 x 2'	11	ITRP06202	8	16'	13
5/8 x 3'	11	ITRP06203	8	24'	20
5/8 x 6'	11	ITRP06206	8	48'	40
5/8 x 10'	11	ITRP06210	8	80'	66
5/8 x 12'	11	ITRP06212	8	96'	80
3/4 x 6'	10	ITRP07506	5	30'	36
3/4 x 10'	10	ITRP07510	5	50'	61
3/4 x 12'	10	ITRP07512	5	60'	73
7/8 x 6'	9	ITRP08706	4	24'	40
1 x 3'	8	ITRP1003	2	6'	12
1 x 6'	8	ITRP1006	2	12'	26
1 x 10'	8	ITRP1010	2	20'	44
1 x 12'	8	ITRP1012	2	24'	52
1-1/8 x 6'	7	ITRP011306	1	6'	16
1-1/4 x 6'	7	ITRP12506	1	6'	20
1-1/4 x 10'	7	ITRP12510	1	10'	35
1-1/4 x 12'	7	ITRP12512	1	12'	42
1-1/2 x 3'	6	ITRP15003	1	3'	15
1-1/2 x 6'	6	ITRP15006	1	6'	30
1-1/2 x 10'	6	ITRP15010	1	10'	50
1-1/2 x 12'	6	ITRP15012	1	12'	60

ITRP | Revision 1.0 | 09.30.25

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. fasteners are manufactured to International Fasteners, Inc.'s performance specifications and print drawings.



Threaded Rod Plain



Meet or exceeds the following specifications:

ASTM A36 Standard specification for carbon structural steel

ASTM A307 Standard specification for carbon steel bolts, studs, and threaded rod with 60,000 PSI tensile strength

Ultimate Values

Diameter	Major Diameter (in)		Recommended Load (lbs)
	MIN	MAX	
3/8"	0.3595	0.3737	730
1/2"	0.4822	0.4985	1350
5/8"	0.6051	0.6233	2160
3/4"	0.7288	0.7482	3230
7/8"	0.8523	0.8731	4480
1"	0.9755	0.9980	5900
1-1/8"	1.0982	1.1228	-
1-1/4"	1.2232	1.2478	-
1-1/2"	1.4703	1.4976	-

ITRP | Revision 1.0 | 09.30.25