



Threaded Rod 304 Stainless Steel



Size	TPI	Part #	QTY / Bundle	FT / Total	LBS / Bundle
1/4 x 6'	20	ITRS02506	50	300'	36
3/8 x 6'	16	ITRS03706	25	150'	43
1/2 x 6'	13	ITRS5006	12	72'	36
1/2 x 12'	13	ITRS5012	12	144'	75
5/8 x 6'	11	ITRS06206	8	48'	40
5/8 x 12'	11	ITRS06212	8	96'	80
3/4 x 6'	10	ITRS07506	5	30'	36
3/4 x 12'	10	ITRS07512	5	60'	73
7/8 x 6'	9	ITRS08706	4	24'	40
7/8 x 12'	9	ITRS08712	4	48'	81
1 x 6'	8	ITRS1006	2	12'	26
1 x 12'	8	ITRS1012	2	24'	52

Meet or exceeds the following specifications:

ASTM F593 Standard specification for stainless steel bolts, hex cap screws, and studs

Ultimate Values

Major Diameter (in)			
Diameter	MIN	MAX	Recommended Load (lbs)
1/4"	0.2367	0.2489	240
5/16"	0.2982	0.3113	400
3/8"	0.3595	0.3737	730
1/2"	0.4822	0.4985	1350
5/8"	0.6051	0.6233	2160
3/4"	0.7288	0.7482	3230
7/8"	0.8523	0.8731	4480
1"	0.9755	0.9980	5900

ITRS | Revision 1.0 | 09.29.25

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. fasteners are manufactured to International Fasteners, Inc.'s performance specifications and print drawings.