

**Threaded Rod
Zinc**

Size	TPI	Part #	QTY / Bundle	FT / Total	LBS / Bundle
1/4 x 2'	20	ITRZ02502	50	100'	12
1/4 x 3'	20	ITRZ02503	50	150'	18
1/4 x 6'	20	ITRZ02506	50	300'	36
1/4 x 10'	20	ITRZ02510	50	500'	60
5/16 x 3'	18	ITRZ03103	35	105'	20
5/16 x 6'	18	ITRZ03106	35	210'	40
5/16 x 10'	18	ITRZ03110	35	350'	68
3/8 x 2'	16	ITRZ03702	25	50'	14
3/8 x 3'	16	ITRZ03703	25	75'	21
3/8 x 6'	16	ITRZ03706	25	150'	43
3/8 x 10'	16	ITRZ03710	25	250'	72
3/8 x 12'	16	ITRZ03712	25	300'	87
7/16 x 3'	14	ITRZ4303	17	51'	20
1/2 x 2'	13	ITRZ5002	12	24'	12
1/2 x 3'	13	ITRZ5003	12	36'	18
1/2 x 6'	13	ITRZ5006	12	72'	36
1/2 x 10'	13	ITRZ5010	12	120'	62
1/2 x 12'	13	ITRZ5012	12	144'	75
5/8 x 2'	11	ITRZ06202	8	16'	13
5/8 x 3'	11	ITRZ06203	8	24'	20
5/8 x 6'	11	ITRZ06206	8	48'	40
5/8 x 10'	11	ITRZ06210	8	80'	66
5/8 x 12'	11	ITRZ06212	8	96'	80
3/4 x 2'	10	ITRZ7502	5	10'	12
3/4 x 3'	10	ITRZ07503	5	15'	18
3/4 x 6'	10	ITRZ07506	5	30'	36

ITRZ | Revision 1.0 | 09.29.25

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. fasteners are manufactured to International Fasteners, Inc.'s performance specifications and print drawings.



**Threaded Rod
Zinc**



Size	TPI	Part #	QTY / Bundle	FT / Total	LBS / Bundle
3/4 x 10'	10	ITRZ07510	5	50'	61
3/4 x 12'	10	ITRZ07512	5	60'	73
7/8 x 3'	9	ITRZ08703	4	12'	20
7/8 x 6'	9	ITRZ08706	4	24'	40
7/8 x 10'	9	ITRZ08710	4	40'	67
7/8 x 12'	9	ITRZ08712	4	48'	81
1 x 3'	8	ITRZ1003	2	6'	12
1 x 6'	8	ITRZ1006	2	12'	26
1 x 10'	8	ITRZ1010	2	20'	44
1 x 12'	8	ITRZ1012	2	24'	52
1-1/8 x 6'	7	ITRZ011306	1	6'	16
1-1/8 x 10'	7	ITRZ011310	1	10'	28
1-1/4 x 6'	7	ITRZ12506	1	6'	20
1-1/4 x 10'	7	ITRZ12510	1	10'	35
1-1/4 x 12'	7	ITRZ12512	1	12'	42
1-1/2 x 3'	6	ITRZ15003	1	3'	15
1-1/2 x 6'	6	ITRZ15006	1	6'	30
1-1/2 x 10'	6	ITRZ15010	1	10'	50
1-1/2 x 12'	6	ITRZ15012	1	12'	60

ITRZ | Revision 1.0 | 09.29.25



Threaded Rod Zinc



Meet or exceeds the following specifications:

ASTM B633 Standard specification for electrodeposited coatings of zinc on iron and steel

Ultimate Values

Diameter	Major Diameter (in)		Recommended Load (lbs)
	MIN	MAX	
1/4"	0.2367	0.2489	240
5/16"	0.2982	0.3113	400
3/8"	0.3595	0.3737	730
7/16"	0.4206	0.4361	-
1/2"	0.4822	0.4985	1350
5/8"	0.6051	0.6233	2160
3/4"	0.7288	0.7482	3230
7/8"	0.8523	0.8731	4480
1"	0.9755	0.9980	5900
1-1/8"	1.0982	1.1228	-
1-1/4"	1.2232	1.2478	-
1-1/2"	1.4703	1.4976	-

ITRZ | Revision 1.0 | 09.29.25