



**INTERNATIONAL  
FASTENERS, INC.**

## Square-Phillips Pancake Head

### Type 17 Point

### 302 Stainless Steel



Size	TPI	Part #	QTY / Carton	Drive
10 x 1"	13	LOPROT17GPSSS1010	5,000	#2 Square-Phillips
10 x 1-1/2"	13	LOPROT17GPSSS10112	2,000	#2 Square-Phillips
10 x 2"	13	LOPROT17GPSSS1020	2,000	#2 Square-Phillips
<b>material:</b>	302 Stainless Steel			
<b>application:</b>	Light metal exterior applications			
<b>installation:</b>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side. The use of impact drivers is not recommended, as they can strip or break the screw.			

#### Meet or exceeds the following specifications:

<b>ASTM A276</b>	Standard specification for stainless steel bars and shapes
<b>ASTM B117</b>	Standard practice for operating salt spray (fog) apparatus
<b>ASTM C1002</b>	Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

#### Ultimate Values

	Diameter	25 Gauge	20 Gauge	3/4" Particle Board	2 x 4 Fir	Minimum Torsional Strength (lb)
<b>Tension (lb) Pullout</b>	#10	173	397	649	547	56
<b>Shear (lb) Bearing</b>	#10	363	834	-	-	56

LOPROT17GPSSS | Revision 1.0 | 09.18.25