



**INTERNATIONAL
FASTENERS, INC.**

Slotted Hex Washer Head

Pierce Point

Zinc Plated



Size	TPI	Part #	QTY / Carton	Drive
7 x 1/2"	16	NDLZ07012	10,000	1/4" Slotted Hex
8 x 1/2"	15	NDLZ08012	10,000	1/4" Slotted Hex
8 x 3/4"	15	NDLZ08034	10,000	1/4" Slotted Hex
8 x 1"	15	NDLZ08100	8,000	1/4" Slotted Hex
8 x 1-1/4"	15	NDLZ08104	5,000	1/4" Slotted Hex
8 x 1-1/2"	15	NDLZ08112	5,000	1/4" Slotted Hex
8 x 2"	15	NDLZ08200	3,000	1/4" Slotted Hex

material: C1022 Low Carbon Steel. Core Hardness: HV240-425

finish: Zinc plating provides 24 hour minimum salt spray corrosion resistance

application: Light metal applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

ASTM C1002 Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

Ultimate Values

		Diameter	25 Gauge	22 Gauge	20 Gauge	Minimum Torsional Strength (lb)
Tension (lb) Pullout	#7	172	260	358	30	
	#8	149	196	367	39	
Shear (lb) Bearing	#7	412	625	628	30	
	#8	337	591	829	39	

NDLZ0708 | Revision 1.0 | 09.03.25



**INTERNATIONAL
FASTENERS, INC.**

Slotted Hex Washer Head

Pierce Point

Zinc Plated



Size	TPI	Part #	QTY / Carton	Drive
10 x 1/2"	12	NDLZ10012	8,000	5/16" Slotted Hex
10 x 3/4"	12	NDLZ10034	6,000	5/16" Slotted Hex
10 x 1"	12	NDLZ1010	5,000	5/16" Slotted Hex
10 x 1-1/2"	12	NDLZ10112	3,000	5/16" Slotted Hex
10 x 2"	12	NDLZ1020	2,500	5/16" Slotted Hex
10 x 3"	12	NDLZ1030	1,500	5/16" Slotted Hex
12 x 1"	11	NDLZ1210	5,000	5/16" Slotted Hex
12 x 1-1/2"	11	NDLZ12112	3,000	5/16" Slotted Hex
12 x 2"	11	NDLZ1220	2,500	5/16" Slotted Hex
12 x 3"	11	NDLZ1230	1,500	5/16" Slotted Hex

material: C1022 Low Carbon Steel, Core Hardness: HV240-425

finish: Zinc plating provides 24 hour minimum salt spray corrosion resistance

application: Light metal applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

ASTM C1002 Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

Ultimate Values

	Diameter	25 Gauge	22 Gauge	20 Gauge	Minimum Torsional Strength (lb)
Tension (lb) Pullout	#10	173	-	363	56
Shear (lb) Bearing	#10	397	-	834	56

NDLZ1012 | Revision 1.0 | 09.03.25