



EPDM Bonded Washer 18-8 Stainless Steel



| Size | Part # | QTY / Carton |
|-------------|-------------|--------------|
| 8-10 x 1/2" | NEOWS1012 | 15,000 |
| 12 x 9/16" | NEOWS120916 | 12,000 |
| 14 x 5/8" | NEOWS1458 | 9,000 |

material: 18-8 Stainless Steel offers optimum corrosion resistance

Meet or exceeds the following specifications:

| | |
|-------------------|---|
| ASTM D412 | Standard specification for vulcanized rubber and thermoplastic elastomers—Tension |
| ASTM D624 | Standard test method for tear strength of conventional vulcanized rubber and thermoplastic elastomers |
| ASTM D573 | Standard test method for rubber—Deterioration in an Air Oven |
| ASTM D792 | Standard test method for density and specific gravity (Relative density) of plastics by displacement |
| ASTM D2240 | Standard test method for rubber property—Durometer hardness |

| Size | Inner Diameter (+/- 0.25 mm) | Outer Diameter (+/- 0.2 mm) | Material Thickness (+/- 0.1 mm) | EPDM Thickness (+/- 0.2 mm) |
|-------------|---------------------------------|--------------------------------|------------------------------------|--------------------------------|
| 8-10 x 1/2" | 5.4 | 12.7 | 0.8 | 2 |
| 12 x 9/16" | 6.1 | 14 | 0.8 | 2 |
| 14 x 5/8" | 7.1 | 16 | 0.8 | 2 |

NEOWS | Revision 1.0 | 10.07.25