



**INTERNATIONAL
FASTENERS, INC.**

Phillips Pan Head with Serrations

Sharp Point

Phosphate Coated



Size	TPI	Part #	QTY / Carton	Drive
7 x 7/16"	23	PFSB07716***	15,000	#2 Phillips
7 x 7/16"	23	PFSB0771610***	10,000	#2 Phillips

material: C1022 Low Carbon Steel, Core Hardness: HV240-425

finish: Phosphate finish provides 48 hour minimum salt spray corrosion resistance

application: Non-load bearing steel framing applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASME B18.6.1	Specification for wood screws
ASTM A510	Specification for general requirements for carbon steel wire rods (Minimum grade 1018)
ASTM B117	Standard practice for operating salt spray (fog) apparatus
ASTM C1002	Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

Ultimate Values

	Diameter	25 Gauge	22 Gauge	20 Gauge	Minimum Torsional Strength (lb)
Tension (lb) Pullout	#7	172	260	358	30
Shear (lb) Bearing	#7	412	625	628	30

PFSB | Revision 1.0 | 09.25.25