



**INTERNATIONAL
FASTENERS, INC.**

**Phillips Thin Wafer Head
Self Drill Point with Wings
Dagger Ultra-Guard Coating™**

Size	TPI	Part #	QTY / Carton	Drive	Drill Point	Max Drill
10 x 1-7/16"	24	PLYSDCTWW101716M	4,000	#2 Phillips	#3	0.175"

material: C1022 Low Carbon Steel. Core Hardness: HV240-425

finish: Dagger Ultra-Guard Coating™ is a zinc/chromate substrate with proprietary organic topcoat, multi step process for use with ACQ treated lumber provides 1000 hour salt spray corrosion resistance

application: Wood to metal applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

ASTM C1513 Specification for steel tapping screws for cold-formed steel framing connections

ASTM F1941 Specification for electrodeposited coatings on threaded fasteners

SAE J78 Standard for dimensional, mechanical, and performance requirements

Ultimate Values

	Diameter	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	Minimum Torsional Strength (lb)
Tension (lb) Pullout	#10	389	554	727	1050	1216	61

PLYSDCTWW | Revision 1.0 | 09.02.25

