



**INTERNATIONAL
FASTENERS, INC.**

Phillips Slotted Truss Head

Break-Away, Type B Point

Zinc Plated



Size	TPI	Part #	QTY / Carton	Drive
8 x 1-3/4"	32	PTBZ08134	4,000	#2 Phillips Slotted

material: C1022 Low Carbon Steel. Unhardened

finish: Zinc plating provides 24 hour minimum salt spray corrosion resistance

application: Knobs and pulls to cabinet drawers, cabinet doors, and other furniture

installation: Snap the screw to the desired length. Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meet or exceeds the following specifications:

ASME B 18.6.1 Specification for wood screws

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

PTBZ08 | Revision 1.0 | 08.30.25



**INTERNATIONAL
FASTENERS, INC.**

Phillips Slotted Truss Head

Break-Away, Type B Point

Zinc Plated



Size	Pitch (metric)	Part #	QTY / Carton	Drive
M4 x 45MM	0.7	PTBZ445MM	4,000	#2 Phillips Slotted

material: C1022 Low Carbon Steel, Unhardened

finish: Zinc plating provides 24 hour minimum salt spray corrosion resistance

application: Knobs and pulls to cabinet drawers, cabinet doors, and other furniture

installation: Snap the screw to the desired length. Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meet or exceeds the following specifications:

ASME B18.6.1 Specification for wood screws

ASTM A510 Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

ASTM B117 Standard practice for operating salt spray (fog) apparatus

PTBZMM | Revision 1.0 | 08.30.25