



**INTERNATIONAL
FASTENERS, INC.**

**Phillips Flat Head
Self Drill Point with Wings
Zinc Plated**

Size	TPI	Part #	QTY / Carton	Drive	Drill Point	Max Drill	Drill Speed
10 x 1-5/8"	16	SD3ZWW10158	3,000	#2 Phillips	#3	0.175"	2500 RPM
12 x 2"	24	SD3ZWW1220	2,000	#3 Phillips	#3	0.210"	1800 RPM
12 x 2-1/2"	24	SD4ZWW12212	1,500	#3 Phillips	#4	0.375"	1500 RPM
1/4 x 2-3/4"	20	SD4ZWW14234	1,000	#3 Phillips	#4	0.375"	1500 RPM
1/4 x 3"	20	SD4ZWW1430	1,000	#3 Phillips	#4	0.375"	1500 RPM
1/4 x 3-1/4"	20	SD4ZWW143104	900	#3 Phillips	#4	0.375"	1500 RPM
1/4 x 3-1/2"	20	SD4ZWW14312	900	#3 Phillips	#4	0.375"	1500 RPM
1/4 x 3-3/4"	20	SD4ZWW14334	500	#3 Phillips	#4	0.375"	1500 RPM

material: C1022 Low Carbon Steel, Core Hardness: HV240-425

finish: Zinc finish provides 24 hour minimum salt spray corrosion resistance

application: Wood to metal applications

installation: Screw gun with depth sensitive nosepiece with installation speed not to exceed listed RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

Meet or exceeds the following specifications:

ASTM A510	Specification for general requirements for carbon steel wire rods (Minimum grade 1018)
ASTM B117	Standard practice for operating salt spray (fog) apparatus
ASTM C1513	Specification for steel tapping screws for cold-formed steel framing connections
SAE J78	Standard for dimensional, mechanical, and performance requirements

Ultimate Values

	Diameter	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	5/32"	3/16"	7/32"	Minimum Torsional Strength (lb)
Tension (lb) Pullout	#10	234	344	482	614	928	-	-	-	61
	#12	-	-	528	778	1120	2118	2350	-	92
	1/4"	-	-	601	896	1445	2500	3520	4115	150

SD4ZWW | Revision 1.2 | 10.31.25

