



**INTERNATIONAL  
FASTENERS, INC.**

**Hex Washer Head**

**Self Drill Point**

**305 Stainless Steel**



Size	TPI	Part #	QTY / Carton	Drive	Drill Point	Max Drill
8 x 1/2"	18	SDSSS080012	10,000	1/4" Hex	#2	0.112"
10 x 3/4"	16	SDSSS10034	5,000	5/16" Hex	#3	0.175"
12 x 3/4"	14	SDSSS12034	5,000	5/16" Hex	#3	0.210"
14 x 3/4"	14	SDSSS14034	2,500	3/8" Hex	#3	0.220"

**material:** 410 Stainless Steel, Case Hardness: HV500 minimum

**application:** Light metal applications in harsh environmental conditions

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 1000 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side. The use of impact drivers is not recommended, as they can strip or break the screw.

**Meet or exceeds the following specifications:**

**ASTM A276** Standard specification for stainless steel bars and shapes

**ASTM B117** Standard practice for operating salt spray (fog) apparatus

**SAE J78** Standard for dimensional, mechanical, and performance requirements

SDSSS | Revision 1.0 | 10.03.25