



**INTERNATIONAL  
FASTENERS, INC.**

## Ultra High Hex Washer Head with Serrations

### Self Drill Point

### Zinc Plated



Size	TPI	Part #	QTY / Carton	Head Height	Drive	Drill Point	Max Drill
10 x 3/4"	16	SDZ10034SMAXS	5,000	0.172" - 0.190"	5/16" Hex	#3	0.175"

**material:** C1022 Low Carbon Steel. Core Hardness: HV240-425

**finish:** Zinc plating provides 24 hour minimum salt spray corrosion resistance

**application:** Metal to metal applications

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side. The use of impact drivers is not recommended, as they can strip or break the screw.

### Meet or exceeds the following specifications:

ICC ESR-4229 

**AC118** ICC-ES Acceptance Criteria for tapping screw fasteners used in steel-to-steel connections

**ASTM A510** Specification for general requirements for carbon steel wire rods (Minimum grade 1018)

**ASTM B117** Standard practice for operating salt spray (fog) apparatus

**ASTM C1513** Specification for steel tapping screws for cold-formed steel framing connections

**SAE J78** Standard for dimensional, mechanical, and performance requirements

### Ultimate Values

	Diameter	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	Minimum Torsional Strength (lb)
<b>Tension (lb) Pullout</b>	#10	389	554	727	1050	1216	61
<b>Shear (lb) Bearing</b>	#10	811	1223	1492	1545	1650	61

SDZSMAXS | Revision 1.0 | 10.03.25