



**Square Trim Head**

**Sharp Point**

**Phosphate Coated**

Size	TPI	Part #	QTY / Carton	Drive
6 x 1"	18	TRSQSB06100	10,000	#1 Square
6 x 1-5/8"	18	TRSQSB06158	5,000	#1 Square
6 x 2-1/4"	18	TRSQSB06214	3,000	#1 Square
8 x 3"	15	TRSQSB08300	2,000	#2 Square

**material:** C1022 Low Carbon Steel, Core Hardness: HV240-425

**finish:** Phosphate finish provides 48 hour minimum salt spray corrosion resistance

**application:** Trim through drywall to 25-20 gauge metal studs

**installation:** Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached. The use of impact drivers is not recommended, as they can strip or break the screw.

**Meet or exceeds the following specifications:**

<b>ASME B18.6.1</b>	Specification for wood screws
<b>ASTM A510</b>	Specification for general requirements for carbon steel wire rods (Minimum grade 1018)
<b>ASTM B117</b>	Standard practice for operating salt spray (fog) apparatus
<b>ASTM C1002</b>	Specification for steel self-piercing tapping screws for application of gypsum panel products or metal plaster based to wood or steel studs

**Ultimate Values**

		Diameter	25 Gauge	22 Gauge	20 Gauge	3/4" Particle Board	2 x 4 Redwood	2 x 4 Fir	Minimum Torsional Strength (lb)
<b>Tension (lb) Pullout</b>	#6	165	245	349	263	204	396	30	
	#8	149	196	367	266	206	398	39	
<b>Shear (lb) Bearing</b>	#6	410	601	620	-	-	-	30	
	#8	337	591	829	-	-	-	39	

TRSQSB | Revision 1.0 | 10.03.25

