



INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Dagger-Tite™ Post Frame Screws • Hex Washer Head Type AB with Bonded Washer • Dagger-Guard Coating™

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point
17 x 1	14	2,000	DAGCT1710TAB	3/8"	Hex Washer	Double Thread	Type AB
17 x 1-1/2	14	1,500	DAGCT17112TAB	3/8"	Hex Washer	Double Thread	Type AB

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Dagger-Guard Coating™ is a three layer, multi step dip/spin bake process which provides 1000 hour salt spray corrosion resistance
<i>application:</i>	metal to wood applications, used to replace 1/4" diameter fasteners where the threads have stripped out.
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meets or exceeds the following specifications:

ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1002	Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs
ASTM F1941	Specification for Electrodeposited Coatings on Threaded Fasteners

Ultimate Value Chart

	DIAMETER	26 Gauge	24 Gauge	22 Gauge	20 Gauge	20 Gauge	20 Gauge	20 Gauge
Tension (Pull) Lbs 1 pc	17-14	225	261	350	442	553	752	1122
Shear (Metal to Metal)	17-14	459	745	989	958	1415	-	-

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.
Appropriate safety factors should be applied to these values for specific purposes.
All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DAGCT17.0923