

**INTERNATIONAL FASTENERS, INC.** 



## SPEC DATA SUBMITTAL SHEET

## Dagger-Tite<sup>™</sup> Post Frame Screws · Hex Washer Head Type 17 · Dagger-Guard Coating<sup>™</sup>

Size	TPI Ctn Qty		Daggerz™ Part Number		Drive	Head	Thread	Point			
9 x 1	15	4,000	DAGCTWOW0910T17		1/4"	Hex Washer	Double Threa	d Type 17			
9 x 1-1/2	15	2,500	DAGCTWOW09112T17		1/4"	Hex Washer	Double Threa	d Type 17			
9 x 2	15	2,000	DAGCTWOW0920T17		1/4"	Hex Washer	Double Threa	d Type 17			
9 x 2-1/2 15		1,500	DAGCTWOW09212T17		1/4"	Hex Washer	Double Threa	d Type 17			
9 x 3	15	1,000	DAGCTWO	V0930T17	1/4"	Hex Washer	Double Threa	d Type 17			
materia	a <i>l:</i> C1	022 LOW CAF	RBON STEEL, CO	ORE HARDN	ESS: HV24	)-425					
<i>finish:</i> Dagger-Guard Coating <sup>™</sup> is a three layer, multi step dip/spin bake process which provides 1000 hour salt spray corrosion resistance											
applicatio	on: me	metal to wood applications									
installatic	on: res	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.									
Meets or e	xceed	s the following	specifications:								
ASTM A51	0		Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)								
ASTM B117		Practice	Practice for Operating Salt Spray (Fog) Apparatus								
ASTM C10	02		Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs								
ASTM F19	41	Specific	Specification for Electrodeposited Coatings on Threaded Fasteners								
Ultimate Va	alue Ci	hart									
		DIAMET	FB Nom	25	22 20	2 x 4 3	3/4" particle 2 x 4	Min Torsiona			

	DIAMETER	Nom Screw Dia	25 Gauge	22 Gauge	20 Gauge	2 x 4 Red Wood	3/4" particle board	2 x 4 Fir	Min Torsional Strength (Lb)
Tension (Pull) Lbs 1 pc	9-15	0.177	149	196	367	206	266	398	39 lbs
Shear (Metal to Metal)	9-15	0.177	337	591	829	-	-	-	39 lbs

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DAGCTWOW.0923