



INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Dagger-Lok™ Wood Screws • Square Flat with Nibs Coarse Type 17 • Lubricized

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point
8 x 3/4*	9	10,000	DLFSQL08034	#2	Flat	Single Lead	Type 17
8 x 1*	9	10,000	DLFSQL08100	#2	Flat	Single Lead	Type 17
8 x 1-1/4	9	7,500	DLFSQL081104	#2	Flat	Single Lead	Type 17
8 x 1-1/2	9	5,000	DLFSQL08112	#2	Flat	Single Lead	Type 17
8 x 1-5/8	9	5,000	DLFSQL081158	#2	Flat	Single Lead	Type 17
8 x 1-3/4	9	4,000	DLFSQL08134	#2	Flat	Single Lead	Type 17
8 x 2	9	3,500	DLFSQL08200	#2	Flat	Single Lead	Type 17
8 x 2-1/4	9	3,000	DLFSQL082104	#2	Flat	Single Lead	Type 17
8 x 2-1/2	9	2,500	DLFSQL08212	#2	Flat	Single Lead	Type 17
8 x 3	9	1,500	DLFSQL08300	#2	Flat	Single Lead	Type 17
10 x 3	8	1,500	DLFSQL1030	#2	Flat	Single Lead	Type 17
10 x 3-1/2	8	1,000	DLFSQL10312	#2	Flat	Single Lead	Type 17
10 x 4	8	1,000	DLFSQL1040	#2	Flat	Single Lead	Type 17

* denotes fully threaded

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Lubricized is a dry touch lubricant which aids in the reduction of torque needed to drill fasteners
<i>application:</i>	wood to wood applications.
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meets or exceeds the following specifications:

ASME B 18.6.1	Standard Specification for Wood Screws
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus

Ultimate Value Chart

DIAMETER	2 x 4 Red Wood Pull Out	3/4 Particle Board Pull Out	2 x 4 Fir Pull Out	Minimum Torsional Strength (Lb)
#8	518	290	540	39
#10	587	388	563	56

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.
Appropriate safety factors should be applied to these values for specific purposes.
All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DLFSQL.0923

TEL (888)241-0203 • FAX (888)241-2096 • EMAIL sales@daggerz.com • WEB www.daggerz.com