

INTERNATIONAL FASTENERS, INC.



SPEC DATA SUBMITTAL SHEET

	Dagge	er-Lok	[™] Wood S	Grews · Square Flat v	vith Nibs	Coarse Ty	/pe 17 · Zinc Point Max Drill	Drill Speed	
			U.20	per Inch Quantity		D1.170 D1.111	- Oline Hilax Dilli	D:::: 0p000	
Size	TI	PI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point	
10 x 1*	8	3	%70 0 5/8	²⁰ DLFL 56021010 ^{TRSQS}		Flat	Single Lead	Type 17	
10 x 1-1/4	8	3	6 x 2-1/4 5,000 8 x 3		#2 #2 #2	Flat	Single Lead	Type 17	
10 x 1-1/2	8	3	4,000	DLFLSQZ10112	#2	Flat	Single Lead	Type 17	
10 x 1-5/8	8	3	4,000	DLFLSQZ101158	#2	Flat	Single Lead	Type 17	
10 x 1-3/4	8	3	3,500	DLFLSQZ10134	#2	Flat	Single Lead	Type 17	
10 x 2	ε	3	3,000	DLFLSQZ1020	#2	Flat	Single Lead	Type 17	
10 x 2-1/2	ε	3	2,000	DLFLSQZ10212	#2	Flat	Single Lead	Type 17	
10 x 3	8	3	1,500	DLFLSQZ1030	#2	Flat	Single Lead	Type 17	
10 x 3-1/2	ε	3	1,000	DLFLSQZ10312	#2 STE	Flat	Single Lead	Type 17	
10 x 4	8	3	1,000	SCREWDLFLGQZ104025 DIAMETER POINT GAUGE (22 #2 20 SAUGE GAUGE	Flat	Single Lead	Type 17	
				#6 #2 128	176 263	426 59	_{8 911} * deր	gtes fully threade	
material:	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425								
finish:	Zinc Finish provides 24 hour minimum salt spray corrosion resistance								
application:	wood to wood applications.								
installation:	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.								
Meets or exce	eeds the	follow	ing specification	ons:					
ASME B 18.6.1 Stan		Stand	ndard Specification for Wood Screws						
		Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)							
ASTM B117		Practice for Operating Salt Spray (Fog) Apparatus							
Ultimate Value	e Chart								
DIAMETER		2 >	4 Red Wood Pull Out	3/4 Particle Board Pull Out		2 x 4 Fir Pull Out		Minimum Torsional Strength (Lb)	
#10			587	388		563	56		

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.

Appropriate safety factors should be applied to these values for specific purposes.

All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DLFLSQZ10.0923